

MOTOROL REFRIN 134A

AUTOMOTIVE REFRIGERATION OIL

Introduction:

Motorol Refrin 134a is specially designed for the Air-conditioning systems of the light vehicles. It provides superior A/c cooling and a smooth operation. It reduces the moisture contamination in the auto A/c systems.

Applications:

It is specially formulated for the Automotive or the Light Trucks Airconditioning systems. Use as per compressor manufacturers guidelines.

Advantages:

- ◆ Low pour point to prevent congealing
- ◆ Provides superior A/c cooling performance
- ◆ Good oxidation, thermal and chemical stability
- ◆ Non Hygroscopic
- ◆ Smoother A/c operation

Performance Standard:

Proprietary Grade

Typical Specifications:

CHARACTERISTICS	Test Method	134A
Color	ASTM D1500	0
Flash Point, (°C), Min	ASTM D92	160
Kinematic Viscosity at 40 °C (cSt)	ASTM D445	48-55
Pour Point (°C), Max	ASTM D97	(-)30
Copper Corrosion	ASTM D130	1A

Environment, Health & Safety:

Every care has been taken to ensure the accuracy of the information in this PDS. This however may be affected by subsequent improvement in product (R&D). MSDS is available for all MOTOROL products on request. MOTOROL products are unlikely to present any health and safety hazard with proper use for the correct application and maintain proper personal hygiene. Do not spill oils on the shop floor, discharge into drains, ground or water sources.